



PRODUCT DATA SHEET F-LON® 6020 Series

F-LON® 6020 is an excellent **Non-Stick** coating. It is a system offering durability and performance in a two layer coating system.

- Good colour stability.
- Good stain resistance.
- Easy application techniques.
- Good resistance to cooking oils, dishwasher detergents and other household chemicals.

F-LON® 6020 was developed for applications which:

- Needs excellent adhesion to most substrates with minimal surface preparation.
- Require an economical, durable non-stick finish.
- Are required to function at elevated temperatures up to 230 °C.
- Need a wear/abrasion resistant coating.

F-LON® 6020 Series

Recommended Dry Film Thickness	22.5 ± 2.5 microns
Substrates	Most metallic substrate.
Pre-treatment	Light gritblast
Application method	Hand spray or automatic spray line.
Curing schedule	375°C - 420°C
Operating Temperature	250°C - Continuous
Colours available	Pale Green
Typical applications	Muffin griddles, muffin cups, hot plates and heat seal platens.
Other properties	Abrasion resistance FDA compliant Hydrophobic

This product data sheet is based on the best information currently available and is offered to users in good faith but without offering or implying a warranty that such information is correct or has not been amended. Nor may it be assumed that patents, copyrights or design registrations concerning systems referred to herein may be ignored.

