

PRODUCT DATA SHEET F-LON® 7070 Series

F-LON® 7070 is an advanced **chemical resistant** coating.

F-LON® 7070 is a high purity fluoropolymer coating based on a unique alternating, copolymer offering excellent capability.

F-LON® 7070 is FDA compliant.

F-LON® 7070 Series

Recommended Dry Film Thickness	0.2 to 1.5mm
Substrates	Most metallic substrates.
Pre-treatment	Degrease followed by sandblasting.
Application method	Hand spray or automatic spray line.
Curing schedule	270°C
Operating Temperature	-40 to + 150°C
Colours available	Pearl grey (others possible)
Typical applications	Pharmaceutical, Food, Fine Chemicals and Semi-conductor process plant demanding high purity and low vapors permeation. Process equipment eg: centrifuge baskets, casings and ancillary equipment.
Other properties	Chemical resistance Abrasion resistance Corrosion resistance FDA Approved



This product data sheet is based on the best information currently available and is offered to users in good faith but without offering or implying a warranty that such information is correct or has not been amended. Nor may it be assumed that patents, copyrights or design registrations concerning systems referred to herein may be ignored.

F-LON® is a registered trademark of Fluorocarbon, Caxton Hill, Hertford, Herts, SG13 7NL