

**PRODUCT DATA SHEET F-LON® 7110 Series**

**F-LON® 7110** is an advanced **chemical resistant** coating.

**F-LON® 7110** is an excellent fluoropolymer two layer coating and conforms to FDA regulations governing coatings for direct food contact application.

**F-LON® 7110 Series**

<b>Recommended Dry Film Thickness</b>	50-75 microns
<b>Substrates</b>	Most metallic substrates.
<b>Pre-treatment</b>	Degrease followed by sandblasting.
<b>Application method</b>	Hand spray or automatic spray line.
<b>Curing schedule</b>	380°C
<b>Operating Temperature</b>	-195°C-260°C
<b>Colours available</b>	Black
<b>Typical applications</b>	Chemical containers, vessels requiring good nonstick and chemical protection.
<b>Other properties</b>	Chemical resistance Abrasion resistance Corrosion resistance Hydrophobic Cryogenic stability FDA compliant

*This product data sheet is based on the best information currently available and is offered to users in good faith but without offering or implying a warranty that such information is correct or has not been amended. Nor may it be assumed that patents, copyrights or design registrations concerning systems referred to herein may be ignored.*

F-LON® is a registered trademark of Fluorocarbon, Caxton Hill, Hertford, Herts, SG13 7NL

