



PRODUCT DATA SHEET F-LON® 9500 Series

F-LON® 9500 has an excellent heat dissipation coating with superior abrasion resistance at **High Temperatures**. It also exhibits high level of hardness and is capable of corrosion & chemical resistance. This product is specifically developed to be applied on exterior or non-functional areas of an **F-LON®** ceramic non-stick coating.

F-LON® 9500 is a patented Ceramic coating based on Sol-Gel technology. Sol-Gel materials are formed from small inorganic particles suspended in solution that gel together to form an inorganic matrix.

F-LON® 9500 is a predominantly inorganic coating with a backbone comprising the elements silicon (Si) and oxygen (O).

F-LON® 9500 Series

Recommended Dry Film Thickness	30 ± 5 µm
Substrates	Most metallic substrates and some plastics.
Pre-treatment	Degrease followed by sandblasting.
Application method	Hand spray or automatic spray line.
Curing schedule	220-280°C
Operating Temperature	450°C
Colours available	Most colors are available
Typical applications	Cookware exterior, Electronic equipment for heat dissipation and electrical isolative properties etc.
Other properties	Corrosion resistance Chemical resistance Abrasion resistance Reach compliant RoHS compliant

*Substrate: Al panel / Coating: Spray, 300°C / 10min / DFT = 30 ± 5 µm.

This product data sheet is based on the best information currently available and is offered to users in good faith but without offering or implying a warranty that such information is correct or has not been amended. Nor may it be assumed that patents, copyrights or design registrations concerning systems referred to herein may be ignored.

